

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
In re Application of Atty. Docket  
CHARALAMPOS POZIDIS NL 000660

Serial No.

Filed: CONCURRENTLY

Title: DETECTION UNIT, DEVICE FOR REPRODUCING AN INFORMATION  
CARRIER AND METHOD FOR DETECTING

Commissioner for Patents  
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to calculation of the filing fee and examination, please  
amend the above-identified application as follows, where marked-up  
version of the amended claim 7 is attached as Appendix A:

IN THE CLAIM

Please amend the claim as follows:

7. (Amended) Device for reproducing an information carrier  
comprising a read head for reproducing a read signal (Sread) from a  
physically detectable pattern in tracks at the information carrier,  
movement means (3) for causing a relative movement between the  
information carrier (1) and the read head (2), a detector according  
to claim 1 for reproducing a binary signal from the read signal, a  
first circuitry module (8.2) for controlling the movement means, a  
second circuitry module (12,13,16,10) for generating an output  
information signal (Sout) from the binary signal by channel  
decoding and/or error correction decoding.

REMARKS

The foregoing amendment to claim 7 was made solely to avoid filing the claim in the multiple dependent form so as to avoid the additional filing fee.

The claim was not amended in order to address issues of patentability and Applicant respectfully reserves all rights she may have under the Doctrine of Equivalents. Applicant furthermore reserves her right to reintroduce subject matter deleted herein at a later time during the prosecution of this application or continuing applications.

Respectfully submitted,

By Michael E. Belk  
Michael E. Belk, Reg. No. 33,357  
Attorney  
(914) 333-9643  
November 24, 2001

## Appendix A

### Version with Markings to Show Changes Made to the Claim

The following are marked up versions of amended claim 7:

7. (Amended) Device for reproducing an information carrier comprising a read head for reproducing a read signal (Sread) from a physically detectable pattern in tracks at the information carrier, movement means (3) for causing a relative movement between the information carrier (1) and the read head (2), a detector according to claim 1 ~~one or more of the claims 1 to 6~~ for reproducing a binary signal from the read signal, a first circuitry module (8.2) for controlling the movement means, a second circuitry module (12,13,16,10) for generating an output information signal (Sout) from the binary signal by channel decoding and/or error correction decoding.

T.03.01.1.2.24.55.0